





strands®




-lighting division






Part No. 270940



Part No. 270941



Part No. 270942



YUKON 2.0 DRIVING LIGHTS LED



PART NO.	270940	270941	270942
VOLTAGE	9-32V DC	9-32V DC	9-32V DC
CONSUMPTION	84 W	86 W	113 W
THEORETICAL LUMEN	9500	11 000	11 500
ACTUAL LUMEN	8000	9500	10 000
KELVIN	5000	5000	5000
1 LUX @	423 m	463 m	1000 m
IP-CLASS	IP68/IP69K	IP68/IP69K	IP68/IP69K
BEAM PATTERN	Flood	Flood	Spot
POSITION LIGHT	No	No	No
CONNECTION	DT-2	DT-2	DT-2
CABLE LENGTH	150 mm	150 mm	150 mm
MATERIAL HOUSING	Aluminium	Aluminium	Aluminium
MATERIAL LENS	Polycarbonate	Polycarbonate	Polycarbonate
DIAMETER	178 mm	229 mm	229 mm
DEPTH	69 mm	97,5/105,5 mm	97,5/105,5 mm
HEIGHT INCLUDING BRACKET	196 mm	249,5 mm	249,5 mm
OPERATING TEMPERATURE	-35°C · +45°C	-35°C · +45°C	-35°C · +45°C
E-APPROVED	ECE R149	ECE R149	No
REF	40	50	-
EMC-CERTIFICATE	ECE R10	ECE R10	ECE R10